

# Official distributor for:



DELO is a world-leading manufacturer of industrial adhesives and specialist in the field of hightech adhesive processes for technical applications

# SIKO - 2-component polyurethane adhesives

### **Technical Data**



## **Properties**

- Polyurethane adhesives provide extremely strong bonding. Even before the adhesive dries and seals completely, the initial bond is strong enough that clamps and other types of securing instruments are unnecessary. This makes manufacturing and construction processes both simpler and cheaper
- ✓ Polyurethane adhesives tend to be very flexible and durable, and they provide good impact resistance
- They vary in degree of resistance to heat and chemicals, as well as in the level of their bulk flexibility

### Application areas

✓ For structural or cosmetic repair of plastic-bumpers, fenders, spoilers, lamp-housings, radiators etc. in the automotive- and other industries where quick cure time on almost any type of plastic material is needed. Also bonds to wood, metal, plastic, fiberglass, ceramic and substrates.

Product	Туре	Viscosity (mPas)	Curing time	Gap fill (MM)	Shear strength- tensile (Kg/cm²)	Temperature range
SIKO S6000-1min	1-min	50.000	1-min	5mm	8.0	-40°C to 120°C Short term to 140°C
SIKO S6000-5min	5-min	50.000	5-min	5mm	8.0	-40°C to 120°C Short term to 140°C

#### **Contact:**

Siko BV 7255 PZ Hengelo (gld) Tel: +31 (0)575 46 20 25 E-Mail: info@sikobv.eu Winkelskamp 1 The Netherlands Fax: +31 (0)575 46 10 87 Internet: www.sikobv.eu